



TACTILE

T100 (GUIDANCE TILE)

T200 (STUDED TILE)

Product Specifications

| Feature | Standard | Results | Notes | |
|---|---------------------------------|-------------------------|----------------|-------------------|
| Safety | | | | |
| Halogen Free | | Yes | | |
| Asbestos Free | | Yes | | |
| This product does not contain PVC, cadmium, formaldehyde, chlorine, fluorine or bromine, which could be highly toxic and corrosive in case of fire. | | | | |
| Fire and Smoke Behaviour | | | | |
| Critical Heat Flux Critical Radiant Flux | ASISO 9239.1-2003 | ≥ 11 kw/m ² | | |
| Smoke Value | ASISO9239.1-2003 | 16 min | | |
| Toxicity of Smoke | Boeing Safety Standard BSS 7239 | ppm level (Complies) | | |
| Mechanical Features | | | | |
| Hardness | ASTM D-2240 | ≥ 85 Shore A | | |
| Dimensional Stability | DIN 51962 | < 0.3 % No variation | | |
| Indentation | ASTM F-36 | ≤ 0.20 mm | | |
| Abrasion Resistance | DIN 53516 | ≤ 160 mm ³ | | |
| Elongation | ASTM D412 | ~150 % | | |
| Tensile Strength | ASTM D-412 | ≥ 800 psi | | |
| Slip Resistance | ASTM D-2047-82 | ≥0.60 R 10 | | Complies with ADA |
| Resistance to Elements Over Time | | | | |
| Colour Fastness | DIN 53389 | 5 - 7 | | |
| Water Retention | ASTM D471 | ≤ 1 % | | |
| Chemical Resistance | DIN 51958 | Good | | See Chart |
| Cigarette Burn Resistance | DIN 51961 | Yes | | Visual Judgment |
| Acoustical Features | | | | |
| Acoustical Insulation | DIN 52210 | ~ 10 dB | Noise abetment | |
| Electrical Features | | | | |
| Insulation | DIN 53596 | ≥ 10 ¹⁰ ohm | Insulating | |
| Static Generation | DIN 54345 | <2 kV | Antistatic | |
| Composition | | | | |
| ACTIVA Rubber flooring products are made of 100% synthetic rubber (SBR - Styrene Butadiene Rubber), the finest quality minerals, organic stabilising agents, vulcanising agents, antioxidants and quality pigments. They DO NOT CONTAIN re-ground rubber, coarse mineral aggregates, fillers, sand or any material known to pose a health hazard in any of the phases of the manufacturing and use cycle. | | | | |

Product Description

TACTILE™ Ground surface
Indicator Rubber complies with AS 1428.4

Features

- Easy Maintenance
- Slip Resistant
- Sound Absorbent
- High durability Compound
- Highly Resilient

Environmental & Safety

Product FREE from:
Halogens, Antimony, Arsenic, Barium, Lead, Cadmium, Chromium, PVC, Volatile elements, DOP's, Formaldehyde, Asbestos and Heavy metals.
Manufactured in compliance with ISO 14001

Information

- Tile Size : 300 x 300 mm
 - Total Thickness :7.0 mm
 - Base Thickness : 2.0 mm
 - Limited Wear Warranty: 1 Year
 - Colour : 4 Standard Colours
- Recommended Adhesives:
Two-part PU
**Please consult our office for detail.*

PRF (Australia)Pty Ltd.

Suite 10, 125 Main St
Blacktown, NSW 2148
P: 02 9671 6900 F: 02 9671 6922
www.rubberflooring.com.au